



LED	Status LED's
1	1 = Interface 2
2	2 = Interface 1
3	3 = Interface 3
4	4 = Interface 4
	<input type="radio"/> Module activated <input type="radio"/> Module deactivated

SW1	Card ID switches																																				
	Use DIP switches 1 to 3 to set the card ID (very useful for remotely identifying individual cards):																																				
	<table border="1"> <thead> <tr> <th>Card-ID</th> <th>0</th> <th>1</th> <th>2</th> <th>3</th> <th>4</th> <th>5</th> <th>6</th> <th>7</th> </tr> </thead> <tbody> <tr> <td>SW1_1</td> <td>OFF</td> <td>ON</td> <td>OFF</td> <td>ON</td> <td>OFF</td> <td>ON</td> <td>OFF</td> <td>ON</td> </tr> <tr> <td>SW1_2</td> <td>OFF</td> <td>OFF</td> <td>ON</td> <td>ON</td> <td>OFF</td> <td>OFF</td> <td>ON</td> <td>ON</td> </tr> <tr> <td>SW1_3</td> <td>OFF</td> <td>OFF</td> <td>OFF</td> <td>OFF</td> <td>ON</td> <td>ON</td> <td>ON</td> <td>ON</td> </tr> </tbody> </table>	Card-ID	0	1	2	3	4	5	6	7	SW1_1	OFF	ON	OFF	ON	OFF	ON	OFF	ON	SW1_2	OFF	OFF	ON	ON	OFF	OFF	ON	ON	SW1_3	OFF	OFF	OFF	OFF	ON	ON	ON	ON
Card-ID	0	1	2	3	4	5	6	7																													
SW1_1	OFF	ON	OFF	ON	OFF	ON	OFF	ON																													
SW1_2	OFF	OFF	ON	ON	OFF	OFF	ON	ON																													
SW1_3	OFF	OFF	OFF	OFF	ON	ON	ON	ON																													

CON1	PCM out
CON2	PCM in
CON3	JTAG
CON4	Additional simholder connector